



CUSHMAN®



# REFRESHER® OASIS™

**DRIVING PROFITS WITH UNMATCHED CAPACITY.**

The Cushman® Refresher® Oasis™ raises the bar for large-volume refreshment vehicles with an industry-leading 500-can capacity, meaning your workers will spend less time refilling the vehicle and more time generating revenue. With the industry's only 72-volt AC electric drivetrain the Oasis delivers unmatched energy efficiency, power and silent performance that supports every round to make those long summer days a breeze.

**LET'S WORK.®**

**72V**  
AC  
ELECTRIC  
OR  
**13.5HP**  
KAWASAKI  
GAS

**12.1**  
SQ. FT.  
COUNTER

**4**  
BEVERAGE  
COMPARTMENTS

**6.7**  
CU. FT.  
DRY STORAGE

**500**  
CAN  
CAPACITY



# CUSHMAN® REFRESHER® OASIS™



**BEVERAGE COMPARTMENT**



**MERCHANDISE CABINET**



**CUSTOMER FRIENDLY WRAP-AROUND COUNTER**

## OPTIONS & ACCESSORIES

- Cup Rack
- Trash/Recycle Bins
- Flat Windshield
- Side Mirrors
- Wrap-Around Counter
- Aluminum Canopy
- Color Options Available for Canopy, Unit & Vehicle
- 3.0 Liter Airpots (2)
- Reversible Airpot Holder
- Humidor
- Consumable Ice Bin
- NSF Rated Ice Sink
- Unique Drainage

	ELECTRIC	GAS
<b>BODY &amp; CHASSIS</b>		
<b>FRAME</b>	Welded Steel with E-Shield™ e-coat plus DuraShield Powder Coat	Welded Steel with E-Shield™ e-coat plus DuraShield Powder Coat
<b>BODY &amp; FINISH</b>	Injection Molded TPO, Painted (front)	Injection Molded TPO, Painted (front)
<b>STANDARD COLOR</b>	Forest Green	Forest Green
<b>DIMENSIONS</b>		
<b>OVERALL LENGTH</b>	117.0 in (297.18 cm)	117.0 in (297.18 cm)
<b>OVERALL WIDTH</b>	50.8 in (129.032 cm)	50.8 in (129.032 cm)
<b>OVERALL HEIGHT (NO CANOPY)</b>	47.4 (120.40 cm)	47.4 (120.40 cm)
<b>OVERALL HEIGHT (WITH CANOPY)</b>	73.3 in (186.18 cm)	73.3 in (186.18 cm)
<b>WHEEL BASE</b>	76 in (193.04 cm)	76 in (193.04 cm)
<b>FRONT WHEEL TRACK</b>	35 in (88.90 cm)	35 in (88.90 cm)
<b>REAR WHEEL TRACK</b>	38.5 in (97.79 cm)	38.5 in (97.79 cm)
<b>GROUND CLEARANCE</b>	4.5 in (11.43 cm)	4.5 in (11.43 cm)
<b>REFRESHER UNIT MATERIAL AND FINISH</b>	5000 Series Aluminum - Super Durable TGIC Polyester Powder Coating	5000 Series Aluminum - Super Durable TGIC Polyester Powder Coating
<b>POWER</b>		
<b>POWER SOURCE</b>	72-Volts	4 Cycle 24.5 cu in (401 cc)
<b>MOTOR TYPE</b>	AC Induction	N/A
<b>VALVE TRAIN</b>	N/A	Single Cylinder OHV
<b>HORSEPOWER (KW)</b>	22.4HP (16.7 kW) - Measured at Peak Torque	13.5 hp (10.1 kW) Exceeds SAE J1940 Standard
<b>ELECTRICAL SYSTEM</b>	72 Volt	Starter/Generator, Solid-State Regulator
<b>BATTERY (QTY/TYPE)</b>	Nine 8-Volt Deep Cycle	One 12 Volt Maintenance Free
<b>BATTERY CHARGER</b>	900 Watt 72V DC	
<b>KEY OR PEDAL START</b>	Pedal	Pedal
<b>AIR CLEANER</b>	N/A	Industrial Rated Dry Filter
<b>LUBRICATION</b>	N/A	Pressurized Oil System
<b>OIL FILTER</b>	N/A	Spin-On
<b>COOLING SYSTEM</b>	Motor Shaft Direct Drive	Air Cooled
<b>FUEL CAPACITY</b>	N/A	6.0 Gallon (22.7 L) tank
<b>DRIVE TRAIN</b>	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
<b>TRANSAXLE</b>	Differential with Helical Gears	Differential with Helical Gears
<b>GEAR SELECTION</b>	Forward-Neutral-Reverse	Forward-Reverse
<b>REAR AXLE RATIO</b>	17:1	16.53:1 (Forward) 16.81:1 (Reverse)
<b>PERFORMANCE</b>		
<b>SEATING CAPACITY</b>	2 Person	2 Person
<b>DRY WEIGHT (w/o batteries)</b>	1105 lb (501.22 kg)	1135 lb (514.83 kg)
<b>CURB WEIGHT</b>	1670 lb (757.50 kg)	1175 lb (532.971 kg)
<b>VEHICLE LOAD CAPACITY</b>	1066 lb (483 kg)	1066 lb (483 kg)
<b>OUTSIDE CLEARANCE CIRCLE</b>	21.5 ft (6.5 m)	21.5 ft (6.5 m)
<b>SPEED</b>	11 mph ± 0.5 mph (17.7 kph ± 0.8 kph)	11 mph ± 0.5 mph (17.7 kph ± 0.8 kph)
<b>STEERING &amp; SUSPENSION</b>		
<b>STEERING</b>	Self-Compensating Rack and Pinion	
<b>FRONT/REAR SUSPENSION</b>	Leaf Springs with Hydraulic Shock Absorbers	
<b>SERVICE BRAKE</b>	Rear Wheel Mechanical Self-adjusting Drum	
<b>PARKING BRAKE</b>	Self-compensating, Single Point Engagement	
<b>TIRES</b>	18 x 8.5-8	