



CUSHMAN®

HAULER® 1200



LOADED WITH RELENTLESS FUNCTIONALITY.

The Hauler® 1200 is equipped to tackle the burden of any job, with a rugged truck-like design. A 12-cubic foot roto-molded bed can easily be customized for every task. Featuring tie-down locations, divider slots and a full line of affordable accessories, transporting everything from loose gravel to small equipment has never been easier. You work hard every day. Let the Hauler 1200 carry the load.

LET'S WORK.®

13.5HP
KAWASAKI
GAS

1500LB
TOW
CAPACITY

12 CU FT
CARGO
BED

1200LB
LOAD
CAPACITY



CUSHMAN® HAULER® 1200



OPTIONAL LADDER RACK/ALUMINUM BED



SIDE FILL GAS TANK



OPTIONAL HYDRAULIC BRAKES



VERSATILE DASH STORAGE

OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet*
- 12-Volt Outlet
- Canopy Storage Net
- Brush Guard*
- Rearview Mirror
- ROPS-Certified Cab
- Ladder/Hoop Rack
- Brake Lights*
- Tail Lights*
- 20" Improved surface tires*
- Large Fender Flare*
- E-Shield™ Frame*
- Fuel/Oil Gauge*
- Premium Steering Wheel*

*Included in Commercial Package



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

| BODY & CHASSIS | |
|--------------------------|--|
| FRAME | Welded Steel with DuraShield™ Powder Coat |
| BODY & FINISH | Injected Molded TPO |
| STANDARD COLOR | Patriot Blue |
| DIMENSIONS | |
| OVERALL LENGTH | 115 in (292.1cm) |
| OVERALL WIDTH | 49.4 in (125.5 cm) |
| OVERALL HEIGHT W/ CANOPY | 70.5 in (179.1 cm) |
| WHEEL BASE | 76.8 in (195.1 cm) |
| FRONT WHEEL TRACK | 35 in (88.9 cm) |
| REAR WHEEL TRACK | 38.5 in (97.8 cm) |
| GROUND CLEARANCE | 3.5 in (8.9 cm) |
| CARGO BOX CAPACITY | 12 cu ft (0.34m ³) |
| POWER | |
| POWER SOURCE | 4-cycle, 24.5 ci (401cc) Cylinder |
| VALVE TRAIN | Single Cylinder OHV |
| HORSEPOWER (KW) | 13.5 hp (10.1 kW) Exceeds SAE J1940 Std. |
| ELECTRICAL SYSTEM | Starter/Generator, Solid-State Regulator |
| BATTERY (QTY/TYPE) | One 12V Maintenance Free |
| KEY OR PEDAL START | Pedal Start |
| AIR CLEANER | Dry Cartridge |
| LUBRICATION | Pressurized Oil System |
| OIL FILTER | Spin-On |
| COOLING SYSTEM | Air Cooled |
| FUEL CAPACITY | 6 Gallon (22.7 L) Tank |
| DRIVE TRAIN | Continuously Variable Transmission (CVT) |
| TRANSAXLE | Differential with Helical Gears |
| GEAR SELECTION | Forward-Reverse |
| REAR AXLE RATIO | 11.42:1(Forward) 15.78:1(Reverse) |
| PERFORMANCE | |
| SEATING CAPACITY | 2 Person |
| CURB WEIGHT | 980 lb (445 kg) |
| BED LOAD CAPACITY | 800 lb (363 kg) |
| VEHICLE LOAD CAPACITY | 1200 lb (545 kg) |
| SPEED | 14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph) |
| TOWING CAPACITY | 1500 lb (680 kg) max |
| OUTSIDE CLEARANCE CIRCLE | 21.5 ft (6.6 m) |
| STEERING & SUSPENSION | |
| STEERING | Self-Compensating Rack and Pinion |
| FRONT/REAR SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers |
| SERVICE BRAKE | Rear Wheel Mechanical Self-adjusting Drum |
| PARKING BRAKE | Self-compensating, Single Point Engagement |
| FRONT/REAR TIRES | 18 x 8.5-8 |

www.cushman.com

©2016 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82290-G5 (Rev. 06/2016)