

**FX-SERIES**

*Specification  
Sheet*

**FX2 26-360  
MIXER**

**ISUZU**

[www.isuzu.co.za](http://www.isuzu.co.za)   

**ISUZU**

*With you, for the long run*

# FXZ 26-360 MIXER

## AXLE LAYOUT

## 6X4

## CONTROL

## FORWARD

### MASS

Permissible Body + Payload (kg)	17 820
Total Tare (T) (kg)	7 680
Front Tare (kg)	4 070
Rear Tare (kg)	3 610
GVM (kg)	25 500
V (kg)	25 500
GCM (kg)	43 500
D/T (kg)	43 500
Front Axle - GA/GAU (kg)	7 500
Front Axle - A/AU (kg)	7 500
Rear Axle - GA/GAU (kg)	21 000
Rear Axle - A/AU (kg)	18 000
Litres of Fuel Tank 1 Included in Tare	15
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
Fifth Wheel Included in Tare	No

### PERFORMANCE

Gradeability @ V (%)	45.19
Gradeability @ D/T (%)	26.49
Max. Geared Road Speed (km/h)	107

### MAJOR DIMENSIONS

Overall Length (mm)	7 790
Overall Width (mm)	2 515
Wheelbase (mm)	4 330
CA - Cab to Bogie/Rear Axle (mm)	3 660
CE - Cab to End of Chassis (mm)	5 640
OH - Overall Height (mm)	2 980
FOH - Front Overhang (mm)	1 480
ROH - Rear Overhang (mm)	1 295
Rear Axle Bogie Spacing (mm)	1 370
1/2 Rear Axle Bogie Spacing (mm)	685
EH - Chassis Rear End Height (mm)	1 133
HH - Ground Clearance (mm)	260
Rear Chassis Width (mm)	850
Turning Radius (Curb to Curb) (mm)	7 700
Turning Radius (Wall to Wall) (mm)	9 600

### ENGINE

Make	Isuzu
Model	6UZ1-TCC
Capacity (cm <sup>3</sup> )	9 839
Layout	Diesel Inline-6
Type	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	265 @ 2 000
Torque @ r/min (Nm)	1 422 @ 1 400
Standard Emissions	Euro 3

### CLUTCH

Make	Exedy
Model	430
Type	Single
Diameter (mm)	430
Operation	Hydraulic Air-Assisted

### TRANSMISSION

Make	ZF
Model	ZF 9 S 1310
Type	Synchromesh
Shift	Manual Gearshift
No. of Gears Forward	9
First Gear Ratio : 1	9.480
Top Gear Ratio : 1	0.750
PTO (Power Take-Off)	Standard

### DRIVE AXLE

Make	Isuzu
Model Axle Front	F075
Model Axle Rear	RT210
Reduction Type	Single
Final Ratio : 1	5.125

### SUSPENSION

Front	Multi-Leaf Springs
Rear	Multi-Leaf Springs
Shock Absorbers	Front & Rear
Stabilisers	Front

### STEERING

Operation	Power
-----------	-------

### BRAKES

System Type	Full Air
Front	Drums
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Spring
Exhaust Brake	Standard
Engine Brake	No
Retarder	Optional

### ELECTRICAL & FUEL

Fuel Tank 1 Capacity (Litres)	200
-------------------------------	-----

### TYRES

Size & Ply Rating - Front	315 / 80 R22.5
Size & Ply Rating - Rear	315 / 80 R22.5

### CAB & EXTRAS

Type	Medium
Roof	Low
No. of Bunks	1
No. of Seats	3
Air-Conditioning	Standard
Driver Airbag	Standard
Radio / CD	Standard
Tachograph	Optional
Tilt Cab	Yes, Hydraulic / Electric with Mechanical Hand Pump